

Medium Power

Portable


Broadband FM

Directional Antenna

Antena Portátil

Direccional

de FM Banda Ancha



This broadband dipole antenna constructed of stainless steel is designed to last a long time in any weather condition. Because of its sturdy construction it can support up to 2 kw of input power with the appropriate connector. Since it has a wide angle of radiation it is strongly recommended for omni-directional arrays. Due to the fact that it is easily disassembled and reassembled, it can be placed in a compact container making it very portable and

inexpensive to ship.

Esta antena dipolo de banda ancha, fabricada de acero inoxidable fue concebida para ser duradera en cualquier condición de clima. Debido a su robusta construcción puede soportar hasta 2 kw de potencia de entrada con el conector apropiado. Esta antena es recomendada para formaciones omnidireccionales ya que tiene un gran ángulo de irradiación. Dado al hecho que es fácil de armar y desarmar esta antena puede ser enviada en un contenedor muy compacto convirtiéndola portátil y económica para envíos.

TECHNICAL SPECIFICATIONS

Antenna type	3 element directional antenna	Front-to-back ratio	18 dB
Frequency range	87.5 - 108 MHz	Lightning protection	all parts grounded
Bandwidth	20 MHz	Max wind velocity	130 mph (208 km/h)
Impedance	50 Ohms	Wind load	48.4 Lbs (22 kg)
Connectors	N type (1 kw) - EIA 7/8 (2 kw)	Wind surface	2.0 ft ² (0.19 m ²)
Power rating	2000 Watts max.	Materials (external)	stainless steel
VSWR	< 1.2 max.	Mounting	from 2" to 4"
Polarization	vertical or horizontal	Weight	20 Lbs (9 kg)
Gain	4.5 dB (referred to half-wave dipole)	Dimensions	50"×72"×3" (1250×1800×60mm)
H plane	150 degrees	Packing	53"×19"×4" (1300×480×100mm)
V plane	70 degrees		

Radiation Patterns (at mid-band)

